




Exterior and Interior Doors From Snorbans

Standard Construction

WOOD VENEERED HOLLOW CORE

APPLICATIONS & BENEFITS

Recommended for a wide range of residential and light commercial applications. The hollow core offers a lightweight option and reduced costs where a light-duty door or bypass door is appropriate. Available in a wide variety of wood species.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

(Nonrated)	
Single doors	4'0" x 10'0"
Regular and Double Egress Paired doors	8'0" x 10'0"

DOOR THICKNESS

1³/₈" and 1³/₄" standard.

STILES

1³/₈" doors: Minimum 1¹/₈" (before trim) clear or fingerjoint stiles.

1³/₄" doors: Minimum 1¹/₄" (before trim) clear or fingerjoint stiles.

Hardwood outer edges compatible with face veneer available upon request.

RAILS

1³/₈" doors: Minimum 2¹/₄" (before trim) mill option fiberboard rails, wood rails available upon request.

1³/₄" doors: Minimum 2⁵/₈" (before trim) mill option softwood rails.

LOOSE LAY CORE AND FRAME ASSEMBLY

Expanded honeycomb core with 5" cell and 3" particle board lockblocks.

FACES

Preggraded: Premium 2-, 3-, or 4-ply veneered skins (minimum 1/60" veneer before sanding). Veneers available in a wide variety of species and cuts.

ADHESIVES

Core and frame assembly and veneer application all with Type II water-resistant adhesives. Type I waterproof adhesive available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement or light cutouts.

FACTORY MACHINING/DETAILING

Complete range of machining capabilities and detailing available.

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

Standard Construction

MOLDED HOLLOW CORE

APPLICATIONS & BENEFITS

Recommended for a wide variety of residential and light commercial applications. The molded panel creates the look of a solid wood interior door, yet offers superior performance to solid wood against moisture related issues. Available in a wide variety of designs with smooth and textured surfaces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

3'0" x 6'8"
3'0" x 7'0"
3'0" x 8'0"

DOOR THICKNESS

1³/₈" and 1³/₄".

STILES

Widths are before trim mill option fingerjoint softwood stiles.

	1 ³ / ₈ "	1 ³ / ₄ "
6'8" high doors	minimum 1 ¹ / ₈ "	minimum 1 ¹ / ₈ "
7'0" high doors	minimum 1 ¹ / ₈ "	minimum 1 ¹ / ₈ "
8'0" high doors	minimum 1 ⁷ / ₈ "	minimum 1 ¹ / ₈ "

RAILS

1³/₈" doors: Minimum 2¹/₄" (before trim) mill option fiberboard rails, wood rails available upon request.

1³/₄" doors: Minimum 2⁵/₈" (before trim) mill option softwood rails.

LOOSE LAY CORE AND FRAME ASSEMBLY

Standard blocking using corrugated pad blocks, with 3" wide particle board lockblocks, see drawings on reverse.

FACES

Pregraded 1/8" Molded Hardboard skins. Available in a wide variety of styles.

ADHESIVES

Core and frame assembly and molded skin application all with Type II water-resistant adhesives. Type I waterproof adhesive is available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement or light cutouts.

FACTORY MACHINING/DETAILING


Complete range of machining capabilities and detailing available.

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

**MOLDED HOLLOW
CORE**


Standard Blocking





• Carmelle **T B**




• Classique **T B**
• 6'8" Cremona **S B**




• Clermont **T B**




• Coventry **■ ■**
• Smooth Coventry **■ ■**



• Colonist **■ ■**
• Smooth Colonist **■ ■**
• Craftmaster Natural **T B**
• Craftmaster Harvest **■ B**



• 7' Smooth Colonist **S B**




• 8' Smooth Colonist **S B**

Standard Construction

WOOD VENEERED BIFOLDS

APPLICATIONS & BENEFITS

Recommended for a wide range of residential and light commercial applications. The hollow core offers a lightweight option and reduced costs where a light duty bifold is appropriate. Available in a wide variety of wood species. Red Oak and Birch bifolds are graded to provide matching panels on all two and four panel sets.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

Two door bifolds	4'0" x 10'0"
Four door bifolds	8'0" x 10'0"

DOOR THICKNESS

1³/₈" standard, 1³/₄" available upon request.

STILES

1³/₈" bifolds: Minimum 1⁵/₁₆" (before trim) mill option softwood stiles.
1³/₄" bifolds: Minimum 1¹/₄" (before trim) mill option softwood stiles.

RAILS

1³/₈" bifolds: Minimum 1⁷/₈" (before trim) mill option fiberboard or softwood rails.
1³/₄" bifolds: Minimum 2⁵/₈" (before trim) mill option softwood rails.

LOOSE LAY CORE AND FRAME ASSEMBLY

Expanded honeycomb core with a 5" cell.

FACES

Pregraded: Premium 2-, 3-, 4-ply veneered skins (minimum 1/₆₀" veneer before sanding). Backs are mill option veneered skins. Matching backs available upon request.

ADHESIVES

Core and frame assembly and veneer application all with Type II water resistant adhesives. Type I waterproof adhesives available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement.

FACTORY MACHINING

Complete range of machining capabilities and detailing available.

HINGES AND HARDWARE

Three edge mounted Stanley butterfly hinges per two panel set, with Stanley 2400 series hardware.

PACKAGING

All bifolds are individually boxed into two door and four door bifold sets, using corrugated boxes.

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

Standard Construction

HARDBOARD AND PREFINISHED BIFOLDS

APPLICATIONS & BENEFITS

Recommended for a wide range of residential and light commercial applications. The prefinished bifold offers consistent quality and reduced onsite finishing costs. Available in a wide variety of finishes. The Unfinished and Primed Hardboard provide excellent paint surfaces for custom finishes.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

Two door bifolds	4'0" x 8'0"
Four door bifolds	8'0" x 8'0"

DOOR THICKNESS

1³/₈" standard, 1³/₄" available upon request.

STILES

1³/₈" bifolds: Minimum 1¹/₈" (before trim) mill option fiberboard stiles, softwood stiles available upon request.

1³/₄" bifolds: Minimum 1¹/₄" (before trim) mill option softwood stiles.

RAILS

1³/₈" bifolds: Minimum 1⁷/₈" (before trim) mill option fiberboard or softwood rails.

1³/₄" bifolds: Minimum 2⁵/₈" (before trim) mill option softwood rails.

LOOSE LAY CORE AND FRAME ASSEMBLY

Expanded honeycomb core with a 5" cell.

FACES

Pregressed: Hardboard, Primed Hardboard, Paper Overlay and Printed Hardboard skins available. Backs are mill option Hardboard skins. Matching backs available upon request.

ADHESIVES

Core and frame assembly and veneer application all with Type II water resistant adhesives. Type I waterproof adhesives available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement.

FACTORY MACHINING

Complete range of machining capabilities and detailing available.

HINGES AND HARDWARE

Three edge mounted Stanley butterfly hinges per two panel set, with Stanley 2400 series hardware.

PACKAGING

All bifolds are individually boxed into two door and four door bifold sets, using corrugated boxes.

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

Standard Construction

MOLDED BIFOLDS

APPLICATIONS & BENEFITS

Recommended for a wide range of residential and light commercial applications. The molded panel creates the look of a solid wood interior bifold, yet offers superior performance to solid wood, against moisture related issues. Available in a wide variety of designs with smooth and textured surfaces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

Two door bifolds	4'0" x 6'8"
	4'0" x 7'0"
	4'0" x 8'0"
Four door bifolds	8'0" x 6'8"
	8'0" x 7'0"
	8'0" x 8'0"

BIFOLD THICKNESS

1³/₈" standard; 1³/₄" available upon request.

STILES

Widths are before trim mill option fingerjoint softwood stiles.

	1 ³ / ₈ "	1 ³ / ₄ "
6'8" high bifolds	minimum 1 ⁵ / ₁₆ "	minimum 1 ¹ / ₄ "
7'0" high bifolds	minimum 1 ⁵ / ₁₆ "	minimum 1 ¹ / ₄ "
8'0" high bifolds	minimum 1 ³ / ₁₆ "	minimum 1 ¹ / ₄ "

RAILS

1³/₈" bifolds: Minimum 1⁷/₈" (before trim) mill option fiberboard or softwood rails.
1³/₄" bifolds: Minimum 2⁵/₈" (before trim) mill option softwood rails.

LOOSE LAY CORE AND FRAME ASSEMBLY

Standard blocking using corrugated pad blocks, see drawings on reverse.

FACES AND BACKS

Faces are pregraded 1/8" Molded Hardboard skins. Backs are mill option pregraded flush Hardboard acclimated to face skin prior to production. Matching backs are available upon request.

ADHESIVES

Core and frame assembly and molded skin application all with Type II water-resistant adhesives. Type I waterproof adhesive is available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement.

HINGES AND HARDWARE

Three edge mounted Stanley butterfly hinges per two panel set, with Stanley 2400 Series hardware.

PACKAGING

All bifolds are individually boxed into two door and four door sets using corrugated boxes.

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

MOLDED BIFOLD

Standard Blocking


MOULDING STYLE

A



Quarter Round

B




Bead & Cove


SURFACE TEXTURE

T Textured surface


S Smooth surface




- Classique **T B**
- 6'8" Cremona **S B**




- Clermont **T B**



- Carmelle **T B**



- Coventry **■ ■**
- Smooth Coventry **■ ■**




- Colonist **■ ■**
- Smooth Colonist **■ ■**
- Craftmaster Natural **■ ■**
- Craftmaster Harvest **T B**

Standard Construction

WOOD VENEER, HARD-BOARD & PREFINISHED PARTICLEBOARD CORE

APPLICATIONS & BENEFITS

Recommended for a wide range of residential and light commercial applications. The particle board core offers good stability against warpage and reduces telegraphing. Available as either nonrated or 20 minute fire-rated in a wide variety of Veneered, Hardboard, and Prefinished faces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

(Nonrated)

Single doors	4'0" x 10'0"
Regular and Double Egress Paired doors	8'0" x 10'0"

(20 minute-rated)

Single doors	4'0" x 10'0"
Maximum size door/transom	4'0" x 10'0"

Paired doors: Dependent on hardware used, up to 8'0" x 10'0"

Note: GP Firestop II meeting edges may be used for 20 minute pairs in lieu of metal edges.

DOOR THICKNESS

1³/₈" (nonrated only) and 1³/₄" standard.

STILES

1³/₈" doors: Minimum 1¹/₈" (before trim) clear or fingerjointed stiles.

1³/₄" doors: Minimum 1¹/₄" (before trim) clear or fingerjointed stiles.

Hardwood outer edges compatible with face veneer available upon request.

RAILS

1³/₈" doors: Minimum 2¹/₄" (before trim) mill option fiberboard or wood rails.

1³/₄" doors: Minimum 2⁵/₈" (before trim) mill option wood rails.

Hardwood rails compatible with face veneer available upon request.

LOOSE LAY CORE AND FRAME ASSEMBLY

Particle board core with an average density of 28 to 34 lbs.

FACES

Pregraded: Hardboard or Premium 2-, 3-, or 4-ply veneered skins (minimum 1/60" veneer before sanding). Veneers available in a wide variety of species and cuts.

ADHESIVES

Core and frame assembly and veneer application all with Type II water-resistant adhesives. Type I waterproof adhesive available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement.

FACTORY MACHINING/DETAILING

Complete range of machining capabilities and detailing available. Rated doors must be in accordance with Warnock Hersey International, Inc. and National Fire Protection Association Standards (NFPA 80, latest edition). Snorbans recommends factory prefitting on all fire doors.

LIGHT OPENINGS

Cutout area may not exceed 40% of the face or half of the door height to comply with the warranty. For 20 minute-rated doors, the total visible area of single or multiple lights may not exceed 1,296 sq. in. per leaf, with a maximum width of 36", or a maximum height of 54". All cutouts must be 6" from the edge of the door or any other cutouts and/or hardware preps. Louvres are not allowed in 20 minute doors.

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

Standard Construction

MOLDED SOLID CORE

APPLICATIONS & BENEFITS

Recommended for a wide range of residential and light commercial applications. The solid core molded panel creates the look of a solid wood interior door with all the advantages of sound retardance and added security, yet with superior performance to solid wood. Available in a wide variety of designs with smooth and textured surfaces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE (Single swing only)
(Rated and nonrated) 3'0" x 6'8"
3'0" x 7'0"
3'0" x 8'0"

DOOR THICKNESS
1³/₈" (nonrated), 1³/₄" (rated and nonrated).

STILES
(Nonrated)
1³/₈" doors: Minimum 1¹/₈" (before trim) mill option fingerjointed softwood stiles.
1³/₄" doors: Minimum 1¹/₄" (before trim) mill option fingerjointed softwood stiles.

STILES
(Rated)
1³/₄" doors 6'8" high: Minimum 1¹/₄" (before trim) mill option fingerjointed softwood stiles.
1³/₄" doors 7'0" and 8'0" high: Minimum 1³/₄" (before trim) mill option fingerjointed softwood stiles.

RAILS
1³/₈" doors: Minimum 1⁷/₈" (before trim) mill option fiberboard or softwood rails.
1³/₄" doors: Minimum 2⁵/₈" (before trim) mill option softwood rails.

LOOSE LAY CORE AND FRAME ASSEMBLY
Particle board core routed to accept molded skins, with an average core density of 28 to 34 lbs.

FACES
Pregraded 1/8" molded hardboard skins. Available in a wide variety of styles.

ADHESIVES
Core and frame assembly and veneer application all with Type II water resistant adhesives. Type I waterproof adhesives available upon request.

BLOCKING
Special inner blocking options may be specified for hardware reinforcement.

FACTORY MACHINING
Complete range of machining capabilities and detailing available. Rated doors must be in accordance with Warnock Hersey International, Inc. and National Fire Protection Agency Standards (NFPA 80, latest edition). Snorbans recommends factory prefitting on all fire doors.


WARRANTY
One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

Standard Construction

WOOD VENEER, HARD-BOARD & PREFINISHED STAVE LUMBER CORE

APPLICATIONS & BENEFITS

Recommended for a wide range of commercial applications. The stave lumber core offers good stability against warpage. Available as either nonrated or 20 minute fire-rated in a wide variety of Veneered, Hardboard, and Prefinished faces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

(Nonrated)	
Single doors	4'0" x 10'0"
Regular and Double Egress Paired doors	8'0" x 10'0"
(20 minute-rated)	
Single doors	4'0" x 10'0"
Maximum size door/transom	4'0" x 10'0"

Paired doors: Dependent on hardware used, up to 8'0" x 10'0"

Note: GP Firestop II meeting edges may be used for 20 minute pairs in lieu of metal edges.

DOOR THICKNESS

1³/₈" (nonrated only) and 1³/₄" standard.

STILES

1³/₈" doors: Minimum 1¹/₈" (before trim) clear or fingerjoint stiles.

1³/₄" doors: Minimum 1¹/₄" (before trim) clear or fingerjoint stiles.

Hardwood outer edges compatible with face veneer available upon request.

RAILS

1³/₈" doors: Minimum 2¹/₄" (before trim) mill option wood rails.

1³/₄" doors: Minimum 2⁵/₈" (before trim) mill option wood rails.

Hardwood rails compatible with face veneer available upon request.

LOOSE LAY CORE AND FRAME ASSEMBLY

A pre-glued, pre-assembled, sanded core made up of softwood strips not more than 2¹/₂" wide, of one species of wood at a 6% to 9% moisture content. The end joints are staggered in adjacent columns.

FACES

Preglued: Hardboard or Premium 2-, 3-, or 4-ply veneered skins (minimum 1/₆₀" veneer before sanding). Veneers available in a wide variety of species and cuts.

ADHESIVES

Core and frame assembly and veneer application all with Type II water-resistant adhesives. Type I waterproof adhesive available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement.

FACTORY MACHINING/DETAILING

Complete range of machining capabilities and detailing available. Rated doors must be in accordance with Warnock Hersey International, Inc. and National Fire Protection Association Standards (NFPA 80, latest edition). Snorbans recommends factory prefitting on all fire doors.

LIGHT OPENINGS

Cutout area may not exceed 40% of the face or half of the door height to comply with the warranty. For 20 minute-rated doors, the total visible area of single or multiple lights may not exceed 1,296 sq. in. per leaf, with a maximum width of 36", or a maximum height of 54". All cutouts must be 6" from the edge of the door or any other cutouts and/or hardware preps. Louvres are not allowed in 20 minute doors.

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted. Warranty is not offered for core telegraphing.

Standard Construction

**WOOD VENEER, HARD-
BOARD & PREFINISHED
45 MINUTE-RATED**

APPLICATIONS & BENEFITS

Recommended for commercial applications that require a 45 minute fire-rated door. Available in a wide variety of Veneered, Hardboard, and Prefinished faces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

Single doors 4'0" x 10'0"
Maximum size door/transom 4'0" x 10'0"
Paired doors: Dependent on blocking and hardware preps. 8'0" x 9'0"
Call Lynden Door, Inc. for further information.

DOOR THICKNESS

1³/₄" standard.

STILES

Untreated softwood stiles. Minimum 1¹/₁₆", maximum 7/8" (after trim). Solid hardwood outer edges matching (compatible with) the face veneer available upon request.

RAILS

Untreated softwood rails. Top rail: Minimum 5/8", maximum 7/8". Bottom rail: Minimum 3/4", maximum 1⁷/₈" (after trim). Matching (compatible) rails available upon request.

LOOSE LAY CORE AND FRAME ASSEMBLY

Stiles, rails, and Georgia Pacific 45 minute mineral core manufactured to fire label requirements.

FACES

Pregraded: Hardboard or Premium 3- or 4-ply veneered skins (minimum 1/60" veneer before sanding). Veneers available in a wide variety of species and cuts.

ADHESIVES

Core and frame assembly and veneer application all with Type II water-resistant adhesives. Type I waterproof adhesive available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement, including lockblocks.

FACTORY MACHINING/DETAILING

Complete range of machining capabilities and detailing available. Rated doors must be in accordance with Warnock Hersey International, Inc. and National Fire Protection Association Standards (NFPA 80, latest edition). Snorbans recommends factory prefitting on all fire doors.

LIGHT OPENINGS

Cutout area may not exceed 40% of the face or half of the door height to comply with the warranty. For 45 minute-rated doors, the total visible area of single or multiple lights may not exceed 1,296 sq. in. per leaf, with a maximum width of 36", or a maximum height of 54". All cutouts must be 6" from the edge of the door or any other cutouts and/or hardware preps with a minimum bottom rail of 10".

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

Standard Construction

**WOOD VENEER, HARD-
BOARD & PREFINISHED
60 MINUTE-RATED**

APPLICATIONS & BENEFITS

Recommended for commercial applications that require a 60 minute fire-rated door. They are available in a wide variety of Veneered, Hardboard, and Pre-finished faces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

Single doors	4'0" x 10'0"
Maximum size door/transom	4'0" x 10'0"
Paired doors: Dependent on blocking and hardware preps.	8'0" x 9'0"

Call Lynden Door, Inc. for further information.

DOOR THICKNESS

1³/₄" standard.

STILES

Firestop II with softwood edges. Maximum 1/2" wood (after trim), with minimum 3/4" composition inner stile. Matching stiles (compatible with) the face veneer available upon request.

RAILS

Firestop II composite rails with optional outer band of softwood. Top rail: Maximum 1/4" optional wood outerband, with a minimum 3/4" composition (after trim). Bottom rail: Minimum 1" composition (after trim), no wood allowed. Matching (compatible) top rail available upon request.

LOOSE LAY CORE AND FRAME ASSEMBLY

Stiles, rails, and Georgia Pacific 60 minute mineral core manufactured to fire label requirements.

FACES

Pregraded: Hardboard or Premium 3- or 4-ply veneered skins (minimum 1/60" veneer before sanding). Veneers available in a wide variety of species and cuts.

ADHESIVES

Core and frame assembly and veneer application all with Type II water-resistant adhesives. Type I waterproof adhesive available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement, including lockblocks.

FACTORY MACHINING/DETAILING

Complete range of machining capabilities and detailing available. Rated doors must be in accordance with Warnock Hersey International, Inc. and National Fire Protection Association Standards (NFPA 80, latest edition). Snorbans recommends factory prefitting on all fire doors.

LIGHT OPENINGS

For 60 minute-rated doors, the total visible area of single or multiple lights may not exceed 100 sq. in. per leaf, with a maximum width of 10", or a maximum height of 33". All cut-outs must be 6" from the edge of the door or any other cutouts and/or hardware preps with a minimum bottom rail of 10".

WARRANTY


One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.

Standard Construction

**WOOD VENEER, HARD-BOARD & PREFINISHED
90 MINUTE-RATED**

APPLICATIONS & BENEFITS

Recommended for commercial applications that require a 90 minute fire-rated door. Available in a wide variety of Veneered, Hardboard, and Prefinished faces.



Doors From Snorbans

Snorbans Joinery L.L.C.
P.O.Box 123463
Dubai, U.A.E.
Tel: 00971 4 3284281
Fax: 00971 4 3284280

SPECIFICATIONS

MAXIMUM SIZE

Single doors	4'0" x 10'0"
Maximum size door/transom	4'0" x 10'0"
Paired doors: Dependent on blocking and hardware preps	8'0" x 9'0"

Call Lynden Door, Inc. for further information.

DOOR THICKNESS

1³/₄" standard.

STILES

Firestop II with softwood edges. Maximum 1/4" wood, minimum 1" composition, (after trim). Matching stiles (compatible with) the face veneer available upon request.

RAILS

Firestop II composite rails with optional outer band of softwood. Top rail: Maximum 1/4" optional wood outerband, minimum 1" composition (after trim). Bottom rail: Minimum 1" composition, no wood allowed. Matching (compatible) top rail available upon request.

LOOSE LAY CORE AND FRAME ASSEMBLY

Stiles, rails, and Georgia Pacific 90 minute mineral core manufactured to fire label requirements.

FACES

Pregraded: Hardboard or Premium 3- or 4-ply veneered skins (minimum 1/60" veneer before sanding). Veneers available in a wide variety of species and cuts.

ADHESIVES

Core and frame assembly and veneer application all with Type II water-resistant adhesives. Type I waterproof adhesive available upon request.

BLOCKING

Special inner blocking options may be specified for hardware reinforcement, including lockblocks.

FACTORY MACHINING/DETAILING

Complete range of machining capabilities and detailing available. Rated doors must be in accordance with Warnock Hersey International, Inc. and National Fire Protection Association Standards (NFPA 80, latest edition). Snorbans recommends factory prefitting on all fire doors.

LIGHT OPENINGS

For 90 minute-rated doors, the total visible area of single or multiple lights may not exceed 100 sq. in. per leaf, with a maximum width of 10", or a maximum height of 33". All cut-outs must be 6" from the edge of the door or any other cutouts and/or hardware preps with a minimum bottom rail of 10".

WARRANTY

One year for interior use only. See warranty terms and conditions. Use of Snorbans interior doors in exterior applications is neither recommended nor warranted.